# Influence of Spatial Variability on the Shear Capacity of RC Members without Shear Reinforcement

Yuguang Yang, Joop den Uijl Joost Walraven, Stavros Petrocheilos \*Structural and Building Engineering – Concrete Structure, Delft University of Technology



### INTRODUCTION

- Shear capacity is critical to RC members without shear reinforcement (such as concrete slab bridges)
- Shear failure is brittle and with large scatter (from beam test results)
- Weak spot of beam specimens may influence the shear behavior

Influence of spatial variability of the shear capacity of RC members Yuguang Yang, Delft University of Technology



# **INTRODUCTION**

- Concrete strength of existing concrete slab bridges tested shows large spacial variability
- Relatively large width of a slab allows force redistribution when local failure happens
- This redistribution effect can hardly be validated in normal slab test, thus special experiment is designed to check this

Influence of spatial variability of the shear capacity of RC members Yuguang Yang, Delft University of Technology



3

## **FEASIBILITY STUDY - ATENA**

- Concrete
- Material Model: 3-D nonlinear cementicious 2
  - Smeared Crack Formulation
  - Crack Band Model
  - Fixed Crack Model
  - Rankind-Fracturing Model for Concrete Cracking
  - · Hordijk Softening Curve
  - Shear Factor  $s_F = 20$ , with shear strength

$$\sigma_{ij} \le \frac{0.18\sqrt{f_c'}}{0.31 + \frac{24w}{a + 16}}, \quad i \ne j$$

Influence of spatial variability of the shear capacity of RC members Yuguang Yang, Delft University of Technology



4

# Reinforcement Material Model: Truss Element Bond Slip Law: CEB-FIP Model Code 1990

slip s


**T**UDelft\_5


 $S_1$ 


Yuguang Yang, Delft University of Technology


 $S_2$ 


Influence of spatial variability of the shear capacity of RC members















FEASIB	EASIBILITY STUDY - ATENA					
Model No.	Layout	P <sub>max</sub>	V <sub>u</sub>	Misc		
C20-60T	a	1160	870.0	First strip in critical shear span start with C20		
C60-20T	a	878	658.5	First strip in critical shear span start with C60		
C60-20-60L	b	1040	780.0	-		
C20-60S	С	1110	832.5	First grid in critical shear span start with C60		
C60-20S	С	907	680.2	First grid in critical shear span start with C20		
C20		853	639.7			
C40		1014	760.5			
C60		1168	876.0			
fluence of spatial variability of the shear capacity of RC members						
guang Yang, Delft University of Technology						











# **CASTING PROCESS**



Influence of spatial variability of the shear capacity of RC members Yuguang Yang, Delft University of Technology



# **CONCRETE MIXTURE**

Mixture of high strength concrete


*Mass* [kg] 280 Content CEM I 52.5 CEM III 42.5 Sand 0-4 mm 775 Gravel 4-16 mm 900 Fly Ash SPL VC 1550 Total


Mixture of low strength concrete


Content	Mass [kg]
CEM I 42.5	150
Limestone Powder	80
Fly Ash	100
Sand 0-4 mm	872
Gravel 4-16 mm	907
Water	185
Total	2294


Influence of spatial variability of the shear capacity of RC members Yuguang Yang, Delft University of Technology























## **CONCLUSIONS**

- The slabs with strips of alternating concrete strength retained the structural integrity.
- The shear capacity of a mixed concrete slab can be evaluated by considering the mean concrete strength.
- The test results clearly show that for structures like slabs with a large width compared to the depth, the shear capacity may be higher than for beam structures and the design formula in Eurocode.

Influence of spatial variability of the shear capacity of RC members Yuguang Yang, Delft University of Technology



# Thanks for your attention, **Questions?**

